


# Product Data Sheet

# Kraloy Hinged Cover Junction Box

Junction boxes and enclosures form an integral part of a circuit protection system and are constructed to provide a degree of protection to personnel against incidental contact with the enclosed equipment and to provide a degree of protection to the enclosed equipment against specified environmental conditions. JBXH boxes are molded of PVC, are entirely non-metallic and provide NEMA Type 1, 2, 3R, 4, 4X, 12, 13 protection.

## **APPLICATION / USE**

JBXH junction boxes are designed and approved for use in indoor/outdoor, industrial, MRO and OEM applications for the accessibility and installation of wire and cable in continuous lengths and to enclose joints and splices. JBXH hinged cover junction boxes can also be used to enclose electrical equipment in non-hazardous locations. The use of a hinged cover box allows for easy access to installed components and protects the contents from the environment.



### **JBXH12128** 278405

### MATERIAL

PVC, Valox, proprietary gasket

**STANDARDS** c(YL)us UL 50/50E, CSA 94.1/94.2, CSA C22.2 No.85, CSA C22.2 No.40

FLAMABILITY RATING UL 94V-0

OUTDOOR SUITABILITY UL 746C

**OPERATING TEMPERATURE** -40°C to 50°C


BOX VOLUME 1,092.9 cu.in/17,909 ml

NEMA Type 1, 2, 3R, 4, 4X, 12, 13

# FASTENER TOOL

#2 Phillips screwdriver

Carton Quantity: 3 Carton Weight: 31.9 lbs / 14.2 kg





kraloyfittings.com