



Kwikflex® NMLT 90° CONDUIT CONNECTORS

FEATURES & BENEFITS


- Available 3/8" through 2"
- All nylon construction resists salt water, weak acids, gasoline, alcohol, oil, grease, & common solvents
- No disassembly required. Instead, the installer simply pushes the conduit or tubing onto the ferrule, tightening the domed sealing nut. The completed assembly can then be secured in the chassis by the locknut (or first secure the connector into a NPT threaded hole)
- No threading of the conduit or tubing required to install, eliminating the possibility of cutting the conduit & creating leak paths
- Standard color - Gray
- Complete conduit/connector system is reusable. Conduit will not wind tight onto the connector during assembly & can be easily removed by pulling while turning in a clockwise direction
- Suitable for indoor/outdoor use; for original equipment manufacturers or field installers
- Lower installed cost
- Molded of type nylon 6. Flammability classification 94V-2; temperature index 125° C
- Smooth internal surfaces for easier wire installation around corner angles
- "O" Ring & steel locknut included

APPLICATIONS

- HVAC equipment
- Machine tools
- Marine equipment
- Motors & controls
- Printing equipment
- Pumps
- Refrigeration equipment
- Assemblies
- Wire hook-up



SPECIFICATIONS



Part No.	Product Code	Trade Size	K.O. Size	Std. Pkg.	Weight / Pkg.	Part Dimensions (inches)		
						A	B	C
LTB03/90	065306	3/8"	1/2"	10/100	5	2.120	0.500	3.120
LTB10/90	065307	1/2"	1/2"	10/100	5	2.120	0.500	3.120
LTB15/90	065310	3/4"	3/4"	10/100	10	2.500	0.520	3.600
LTB20/90	065312	1"	1"	5/50	8	3.125	0.700	4.125
LTB25/90	065314	1-1/4"	1-1/4"	5/25	7	4.450	0.760	5.200
LTB30/90	065317	1-1/2"	1-1/2"	2/10	4	4.750	0.800	5.200
LTB35/90	065320	2"	2"	2/10	5	5.420	0.860	5.800

Available in Black upon request